


# Aluminum Channel

## 6061-T6 Aluminum Association Channel - Canadian



■ Specifications: ASTM B 221

■ Stocked in 20 foot lengths

Size (A)	Web (B)	Flange (C)	Thickness (D)	Radius (R)	Lbs/Ft	Lbs/Length	Part Number Canada	Length	Profile
2	.130	1.000	.130	.100	0.577	14.425	754170*	25 ft	
2	.170	1.250	.260	.150	1.071	26.775	542264*	25 ft	
2 1/2	.1875	1.500			1.059	21.180	515071	20 ft	Rounded Corners
3	.130	1.500	.200	.250	1.135	28.375	556661*	25 ft	American Standard
3	.170	1.750	.260	.250	1.597	39.925	543464*	25 ft	
3	.1875	1.500	.250	.312	1.484	29.680	515089	20 ft	
3	.250	1.500	.312	.312	1.849	36.980	515136	20 ft	
3	.250	2.000	.312	.188	2.184	43.680	515144	20 ft	
3	.356	1.596	.170	.270	2.074	51.850	540797	20 ft	American Standard
4	.150	2.000	.230	.250	1.738	43.450	552120*	25 ft	
4	.1875	1.625	.281	.375	1.905	38.100	515097	20 ft	
4	.1875	2.000	.250	.375	2.012	40.240	515102	20 ft	
4	.1875	2.000	.250	.375	2.012	48.288	729028**	24 ft	
4	.190	2.250	.290	.250	2.331	58.275	541006*	25 ft	
4	.250	2.000	.312	.375	2.531	50.620	515152	20 ft	
5	.150	2.250	.260	.300	2.212	55.300	543838*	25 ft	
5	.1875	2.000	.312	.375	2.506	50.120	515110	20 ft	
5	.190	2.750	.320	.300	3.089	77.225	543820*	25 ft	
5	.281	2.000	.343	.375	3.109	62.180	515178	20 ft	
6	.170	2.500	.280	.300	2.834	70.850	542230*	25 ft	
6	.210	3.250	.350	.300	4.030	100.750	542036*	25 ft	
6	.250	2.500	.312	.437	3.512	70.240	515160	20 ft	
6	.281	2.000	.375	.437	3.595	71.900	515186	20 ft	
6	.375	3.500	.500	.437	6.417	128.340	515225	20 ft	
7	.210	3.500	.380	.310	4.715	117.875	527353*	25 ft	
8	.190	3.000	.350	.300	4.147	103.675	544135*	25 ft	
8	.250	3.750	.410	.350	5.789	144.725	541048*	25 ft	
8	.281	3.000	.437	.500	5.565	111.300	515194	20 ft	
9	.230	3.250	.350	.350	4.983	124.575	543040*	25 ft	
10	.250	3.500	.410	.350	6.136	153.400	604545*	25 ft	
10	.281	3.000	.437	.500	6.224	124.480	515209	20 ft	
10	.310	4.250	.500	.400	8.360	209.000	552138*	25 ft	
12	.290	4.000	.470	.400	8.274	206.850	515217*	25 ft	
12	.300	2.960	.280	.380	7.415	295.550	541056*	25 ft	American Standard
12	.375	4.000	.562	.625	10.280	205.600	515233	20 ft	


\* Stocked in 25 foot lengths

\*\* Stocked in 24 foot lengths

Dimensions are in inches. All weights are approximate.

# Aluminum Channel

## 6063 -T52 Sharp Corner Architectural Channel - Canadian



- Specifications: ASTM B 221
- Stocked in 20 foot lengths

Size (A)	Web (C)	Flange (B)	Lbs/Ft	Lbs/Length	Part Number Canada
1/2	.094	1/2	0.145	2.900	515267
1/2	.125	3/4	0.263	5.260	515291
3/4	.125	1/2	0.221	4.420	515306
3/4	.125	3/4	0.300	4.800	515275
7/8	.125	7/8	0.356	7.120	515283
1	.125	1/2	0.257	5.140	515314
1	.125	3/4	0.331	6.620	515322
1	.125	1	0.413	6.608	515330
1 1/4	.125	1/2	0.300	6.000	515348
1 1/4	.125	5/8	0.338	6.760	515356
1 1/4	.125	1 1/4	0.526	8.416	515364
1 1/2	.125	1/2	0.337	6.740	515372
1 1/2	.080	3/4	0.270	5.400	599211
1 1/2	.080	3/4	0.270	5.940	515259
1 1/2	.080	3/4	0.305	7.625	552146
1 1/2	.125	3/4	0.413	8.260	515380
1 1/2	.125	1	0.487	7.792	515398
1 1/2	.125	1 1/2	0.637	10.192	515403
1 3/4	.125	3/4	0.453	9.060	515411
1 3/4	.125	1	0.510	8.160	628808*
2	.125	1/2	0.404	8.080	515437
2	.125	1	0.564	9.024	515445
2 1/2	.125	1 1/2	0.787	12.592	610960*
2	.125	2	0.863	17.260	566666
2	.250	2	1.670	36.740 **	595908**
3	.125	1	0.718	11.488	515453
3	.125	2	0.992	19.840	515461

\* Stocked in 16 foot lengths

\*\* Stocked in 22 foot lengths

Dimensions are in inches. All weights are approximate.