


## Aluminum Rod & Bar

### 5083- H111 Aluminum American Standard Straight Stem and Flange Tee Bar




- Specifications: ASTM B 221
- Stocked in 25 foot lengths

Stem (A)	Flange (B)	Thickness (C)	Thickness (D)	Thickness (E)	Radius (R)	Lbs/Ft	Lbs/Length	Part Number
6	4 1/2	.219	.291	.219	.329	3.065	76.625	772788

Dimensions are in inches. All weights are approximate.

### 5086- H111 Aluminum American Standard Straight Stem and Flange Tee Bar



- Specifications: ASTM B 221
- Stocked in 25 foot lengths


Stem (A)	Flange (B)	Thickness (C)	Thickness (D)	Thickness (E)	Radius (R)	Lbs/Ft	Lbs/Length	Part Number
3	1 1/2	1.500	.257	.188	.282	1.500	30.000	754057*
3	3	.250	.250	.250	.250	1.720	43.000	701957
4	3	.188	.188	.188	.125	1.501	37.525	667593
4	4	.188	.254	.188	.282	2.063	51.575	679972
5	4 1/2	.188	.254	.188	.282	2.500	62.500	765757
6	4	.375	.375	.375	.312	4.294	107.350	676665
6	4 1/2	.219	.291	.219	.329	3.065	76.625	667569
8	4 3/4	.258	.300	.258	.387	4.000	100.000	779308
8	4 3/4	.277	.459	.277	.416	5.107	127.675	667585
8	6	.500	.500	.500	.250	7.806	195.150	683167
9	2 1/2	.313	.312	.312	.250	4.135	103.375	682763
10	5	.324	.352	.324	.486	5.750	143.750	695758
12	5	.391	.457	.391	.587	8.085	202.125	688939

Dimensions are in inches. All weights are approximate.

\* Stocked in 20 foot lengths

## Aluminum Rod & Bar

### 5086- H111 Aluminum Standard Sharp Corners Straight Stem and Flange Tee Bar




- Specifications: ASTM B 221
- Stocked in 25 foot lengths

Stem (A)	Flange (B)	Thickness (C)	Thickness (D)	Thickness (E)	Radius (R)	Lbs/Ft	Lbs/Length	Part Number
2	1	.188	.188	.188		.653	13.060	753417*
3	2	.250	.250	.250		1.397	34.925	671534
4	2	.250	.250	.250		1.690	42.250	670504
6	2	.250	.250	.250		2.278	56.950	670512
6	2	.375	.375	.375		3.362	84.050	670520
12	2 1/2	.500	.500	.500		8.094	202.350	683159

Dimensions are in inches. All weights are approximate.

\* Stocked in 20 foot lengths

### 5086- H111 Aluminum American Standard Tapered Stem and Flange Tee Bar



- Specifications: ASTM B 221
- Stocked in 25 foot lengths

Stem (A)	Flange (B)	Thickness (C)	Thickness (D)	Thickness (E)	Radius (R)	Lbs/Ft	Lbs/Length	Part Number
1 1/2	1 1/2	.188	.219	.219	.188	.693	17.325	630279
1 1/2	1 1/2	.250	.219	.219	.188	.870	21.750	635601
2	2	.250	.312	.312	.240	1.235	30.875	630287
2 1/2	2 1/2	.313	.375	.375	.250	1.905	47.625	716481
3	1 1/2	.188	.219	.219	.188	.971	24.275	803181
3	2	.250	.313	.313	.250	1.428	35.700	803199
3	3	.375	.438	.438	.312	2.717	67.930	636097
4	2	.250	.313	.313	.250	1.956	48.900	803173
4	4	.375	.438	.438	.500	3.740	93.500	661767
6	4	.250	.313	.313	.250	3.240	81.000	803149

Dimensions are in inches. All weights are approximate.